

OUTDOOR | WALL MOUNTED

1450 Watt

IP Enclosures air conditioners are designed for the cooling needs of electrical cabinets, optimised for door or side-panel mounting and have been designed for high efficiency and low maintenance. They are made in Italy and are SAA approved and certified for use in New Zealand.

Features	Unit	IP-ACOWM145
Power supply	V/Hz	230V/1ph/50-60
Dimensions HxWxD	mm	800x400x240
Cooling capacity EN14511 A35A35	W	1450/1500
Cooling capacity EN14511 A35A50	W	1150/1200
Air flow rate (free blow) enclosure	m ³ /h	600/625
Max current	A	3.7/4.2
Delayed fuse	A	10
Absorbed electric power EN14511 A35A35	W	660/690
Absorbed electric power EN14511 A35A50	W	800/850
Refrigerant (type/charge)	-/g	R134a/700g
Operating temperature (ambient)	°C	+5/+55
Operating temperature (enclosure)	°C	+20/+45
Temperature controller (factory set at 35°C)	-	Integrated digital thermostat
Compressor type	-	Rotative Compressor
Electrical connection	-	Three-pole connector
Protection degree EN60529/1 enclosure side	-	IP54
Protection degree EN60529/1 ambient side	-	IP34
Weight (with packaging)	kg	37
Colour	-	RAL 7035
Conformity/Certifications	-	SAA, CE, AS/NZS60335.2.40:2019, AS/NZS60335.1:2020

