

# SSDW 19" Data Rack

# IP-SSDW6RU30

STAINLESS STEEL | WALL MOUNT | SINGLE DOOR | IP66

19" 6RU x 300D

IP Enclosures SSDW range of stainless steel IP66 19" data racks are designed for extreme duty to house sensitive data network equipment in harsh environments. They are suitable for internal and external installations. All IP Enclosures are built to precision to ensure consistent high quality standards.

**Protection:** IP66 IK10

**Standards (& Conformities):** IEC/EN 60529, IEC/EN 62208, EIA-310-D, RoHS



**Rack Unit Size:** 6RU

**Material:**

- Enclosure Body: 1.5mm grade 316L stainless steel
- Enclosure Door: 1.5mm grade 316L stainless steel
- 19" Data Rack Rails: 2.0mm galvanised steel sheet
- Gland Plate: 1.5mm grade 316L stainless steel
- Enclosure Seal: Polyurethane

**Surface Finish:** 0.4 micron Ra surface brushed finish.

**Body & 19" Rails:** The robust monoblock body is fabricated using 1.5mm grade 316L stainless steel. Cutting, pressing and full continuous seam welding using precision automated manufacturing equipment ensures accuracy and consistent high quality. Flat face sealing surfaces are provided to increase seal life. A stainless steel gland plate is also incorporated into the bottom face. 19" data rack rails are fitted. (600mm deep racks include front and rear rails).

**Enclosure Door:** The robust surface mounted door is fabricated using 1.5mm grade 316L stainless steel and incorporates concealed removable hinges with captive pins. Doors are also designed for a 110° opening. Door with windows are available as an accessory.







**Enclosure Seal:** A high quality machine-applied full perimeter UL listed Polyurethane seal foamed in place (FIP) provides excellent sealing over a long life. Temperature resistance -40°C to 80°C (160°C short term loading).

**Enclosure Lock:** Grade 316L stainless steel 8mm square drive quarter turn lock with key.

**Gland Plate:** Gland plate is incorporated into the bottom face of the enclosure for cable management. It is provided with gaskets and fasteners. The size and quantity vary according to enclosure size.

**Mass:** 17.0Kg.

**Maximum Weight of Contents:** 95.4Kg.



# SSDW 19" Data Rack

# IP-SSDW6RU30

STAINLESS STEEL | WALL MOUNT | SINGLE DOOR | IP66

19" 6RU x 300D

## ACCESSORIES:

Part Number	Description
IP-SDDINPANEL1	1RU 19" DIN Terminal Rail
IP-SDCOVER1	1RU 19" Cover Panel
IP-EMH1	1RU 19" Cover Panel (Ventilated)
IP-SDDINPANEL2	2RU 19" DIN Terminal Rail
IP-SDCOVER2	2RU 19" Cover Panel
IP-EMH2	2RU 19" Cover Panel (Ventilated)
IP-SDDINPANEL3	3RU 19" DIN Terminal Rail
IP-SDCOVER3	3RU 19" Cover Panel
IP-EMH3	3RU 19" Cover Panel (Ventilated)
IP-SDDP3	3RU 19" Distribution Board (Supplied with Cover Panel)
IP-SDDINBOX4RU	4RU 19" Rack Mounted DIN Rail Housing
IP-SDBOX4RU	4RU 19" Rack Mount Housing
IP-SDDINBOX6RU	6RU 19" Rack Mounted DIN Rail Housing
IP-SDBOX6RU	6RU 19" Rack Mount Housing
IP-RCLF120	1RU 19" Fixed Shelf; 200mmD
IP-RNG1U19	1RU Cable Organiser for Data Rack
IP-M6SCREW-CAGENUT	M6 Cage Nut and Screw for 19" Data Racks - Pack of 50

## CERTIFICATES:

IEC 60529 Degrees of protection provided by enclosures: Certificate AB-0386-T 2311.14.01/00

IEC/EN 62208 Empty Enclosures for low-voltage switchgear and controlgear assemblies: Certificate 0366932-TSE-01/01

CE Certificate of Compliance: Certificate SZT-24 MA 33485-1

UKCA Certificate of Compliance: Certificate SZT-25 MA 38734-1

Products are manufactured to Quality, Safety and Environmental Standards.

**WARRANTY:** 5 years.