

204mmH x 204mmW x 37mmD

IP Enclosures provide a wide range of ventilation products for electrical enclosures. The range consists of a modern Italian design with minimal external projection and allows for easy filter maintenance due to a front-opening grille. The configuration of the grille, seal gasket and filter mat provide an IP54 protection. All moulded parts are made of highly resistant and self-extinguishing ABS. IP Enclosures ventilation products are manufacture to the highest quality in Italy.

Standards: EN60335-1, EN55014, EN6100-3-2, EN60529, Compliant to relevant Australian Standards, CE


Material: ABS, Self-extinguishing UL94V-0, RAL7035 Grey

Protection: IP54


Standard Filter: Self-extinguishing G3 synthetic fibre mat

| Features | Unit | IP-V3000 |
|--------------------------------|---------|------------------------------|
| Air flow rate (free blow) | m3/h | - |
| Air flow rate with exit filter | m3/h | - |
| Power supply | V/Hz | - |
| Dimensions HxWxD | mm | 204x204x37 |
| Power consumption | W | - |
| Current consumption | A | - |
| Overcurrent protection | - | - |
| Electrical connection | - | - |
| Duty cycle | - | - |
| Operating temperature | °C (°F) | -10 / +70 (+14 / +158) |
| Protection degree / Class | - | IP54 |
| Noise level | dB(A) | - |
| Flow direction | - | - |
| Bearing | - | - |
| Filter mat EN779 | - | G3 |
| Service life (at 40°C) | hr | - |
| Material | - | ABS UL94V-0; Colour RAL7035 |
| Wall thickness | mm | 1.2 - 2.4 |
| Gasket | - | foam seal gasket |
| Weight (with packaging) | kg | 0.32 (0.42) |
| Package dimensions H x W x D | mm | 220x220x43 |
| Mounting | - | fast clip-on |
| Conformity/Certifications | - | (Refer to the details above) |


*0.5-2.5mm²




FRONT VIEW



SIDE VIEW



CUT-OUT DIMENSION



Easy Maintenance



1. Open Grille



2. Remove Filter



3. Insert Filter



4. Close Grille