



PRODUCT BROCHURE

Stainless Steel Pushbutton Enclosures
& Terminal Boxes

IP66-IP67 Pushbutton Enclosures

SSP

Stainless Steel Grade 304

IP66, IP67 | 22.5mm Hole



Features & Specifications

The IP Enclosures SSP range of grade stainless steel pushbutton enclosures are ideal for use in the harshest environments. The silicon seal gasket is resistant to harsh chemicals. They are available in 1 hole, 2 hole, 3 hole, 4 hole, 6 hole and 8 hole configurations.

Protection: IP66, IP67, NEMA 4x.

Standard: UL508A



Material:

- Body: 1.0mm Grade 304 & 316L Stainless Steel. Surface Finish: 0.2 microns
- Lid/Door: 1.0mm Grade 304 & 316L Stainless Steel
- Seal: Silicone

Body: The robust body is fabricated using 1.0mm Grade 304 & 316L Stainless Steel. Flat face sealing surfaces are provided to increase seal life. A stainless steel gland plate is also incorporated into the bottom face. Adjustable 19" data rack rails are provided fitted. 600mm deep racks include front and rear rails.

Lid/Door: The robust pre-drilled lid/door is fabricated using 1.0mm Grade 304&316L Stainless Steel and is fastened using screws.

Hole Diameter: 22.5mm (30.5mm available upon request)

Seal: High quality Silicone seal.

Accessories: Wall Mounting Brackets. SKU: IP-HWMB (Set of 2)

Surface Roughness: 0.2 micron

FLAT ROOF

Part Number	Optional	Size	Description
Grade 304	Grade 316L	HxWxD	Hole & Columns
IP-304-P1	IP-SSP1	90 x 90 x 90	1 Hole
IP-304-P2	IP-SSP2	140 x 90 x 90	2 Hole
IP-304-P3	IP-SSP3	160 x 160 x 100	3 Hole
IP-304-P4	IP-SSP4	140 x 90 x 90	4 Hole
IP-304-P2X2	IP-SSP2X2	200 x 200 x 100	4 Hole (2 Columns of 2)
IP-304-P3X2	IP-SSP3X2	280 x 90 x 90	6 Hole (3 Columns of 2)
IP-304-P4X2	IP-SSP4X2	250 x 160 x 100	8 Hole (4 Columns of 2)



IP66-IP67 Terminal Boxes

Stainless Steel Grade 304

SST

SCREWED LID | IP66, IP67



The IP Enclosures SST range of stainless steel terminal boxes are designed for use in the most demanding industrial environments.

Features & Specifications

The IP Enclosures range of grade stainless steel terminal boxes are designed for use in the most demanding industrial environments.

Protection: IP66, IP67, NEMA 4x.

Standard: UL508A



Material:

- Body: 1.0mm Grade 304 & 316L Stainless Steel. Surface Finish: 0.2 microns
- Lid/Door: 1.0mm Grade 304 & 316L Stainless Steel
- Seal: Silicone

Body: The robust body is fabricated using 1.0mm Grade 304 & 316L Stainless Steel. Flat face sealing surfaces are provided to increase seal life. A stainless steel gland plate is also incorporated into the bottom face. Adjustable 19" data rack rails are provided fitted. 600mm deep racks include front and rear rails.

Lid/Door: The robust pre-drilled lid/door is fabricated using 1.0mm Grade 304 & 316L Stainless Steel and is fastened using screws.

Seal: High quality Silicone seal.

Accessories: Wall Mounting Brackets. SKU: IP-HWMB (Set of 2)

Surface Roughness: 0.2 micron



Part Number	Optional	Size
Grade 304	Grade 316L	HxWxD
IP-304-T090909	IP-SST090909	90 x 90 x 90
IP-304-T140909	IP-SST140909	140 x 90 x 90
IP-304-T200909	IP-SST200909	200 x 90 x 90
IP-304-T280909	IP-SST280909	280 x 90 x 90
IP-304-T101010	IP-SST101010	100 x 100 x 100
IP-304-T161010	IP-SST161010	160 x 100 x 100
IP-304-T161610	IP-SST161610	160 x 160 x 100
IP-304-T251610	IP-SST251610	250 x 160 x 100
IP-304-T202010	IP-SST202010	200 x 200 x 100
IP-304-T202015	IP-SST202015	200 x 200 x 150
IP-304-T402012	IP-SST402012	400 x 200 x 120
IP-304-T403012	IP-SST403012	400 x 300 x 120
IP-304-T404012	IP-SST404012	400 x 400 x 120

Note: This size does not include device mounting plate



IP ENCLOSURES PTY LTD

ABN 17 168 921 319

Head Office: 19-27 Fren Chaplin Circuit, Bells Creek QLD 4551

sales@ipenclosures.com.au | www.ipenclosures.com.au

T: 1300 576 094 | + 61 7 5450 1489

GLOBAL DISTRIBUTION: UK Europe USA UAE NZ Asia-Pacific